

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (Currently Amended) A method for building an information network via an antenna terminal or an antenna cable disposed in a house for receiving television broadcasting or radio broadcasting, the method comprising:

step (a) of selecting at least one frequency not used by television broadcasting or radio broadcasting in an area where the house is located;

step (b) of encoding transmission data;

step (c) of generating a carrier wave having the frequency selected in step (a);

step (d) of modulating [[a]]said carrier wave having the frequency selected in step (a) by using said encoded transmission data;

step (e) of~~transmitted from a first information terminal and~~ transmitting the modulated carrier wave via the antenna terminal or the antenna cable from a first information terminal; and

~~step (e) of~~(f) of receiving the carrier wave transmitted in step (b) and demodulating the carrier wave to produce reception data received by a second information terminal.

2. (Original) The method according to claim 1, wherein, in step (a), at least one of frequencies for channels not used by the television broadcasting or radio broadcasting in an area where the house is located is selected.

3. (Original) The method according to claim 1, further comprising a step of bidirectionally transmitting data between the information network via the antenna terminal or the antenna cable and another network by converting the format of the data.

4. (Currently Amended) A method for building an information network via an antenna terminal or an antenna cable disposed in a house for receiving television broadcasting or radio broadcasting, the method comprising:

step (a) of selecting a first frequency and a second frequency not used by television broadcasting or radio broadcasting in an area where the house is located;

step (b) of encoding transmission data;

step (c) of generating a carrier wave having the first frequency selected in step (a);

step (d) of modulating [[a]]said carrier wave having the first frequency by using said encoded transmission data transmitted from a first information terminal and transmitting the modulated carrier wave via the antenna terminal or the antenna cable;

step ~~[[c]]~~(e) of receiving the carrier wave transmitted in step ~~[[b]]~~(d) and demodulating the carrier wave to produce reception data received by a second information terminal;

step ~~[[d]]~~(f) of encoding transmission data;

step (g) of generating another carrier wave having the second frequency selected in step (a);

step (h) of modulating [[a]]said carrier wave having the second frequency by using said encoded transmission data transmitted from the second information terminal and transmitting the modulated carrier wave via the antenna terminal or the antenna cable; and

step ~~[(e)]~~(i) of receiving the carrier wave transmitted in step ~~[(d)]~~(h) and demodulating the carrier wave to produce reception data received by the first information terminal.

5. (Original) The method according to claim 4, wherein, in step (a), at least one of frequencies for channels not used by the television broadcasting or radio broadcasting in an area where the house is located is selected.

6. (Original) The method according to claim 4, further comprising a step of bidirectionally transmitting data between the information network via the antenna terminal or the antenna cable and another network by converting the format of the data.

7. (Currently Amended) A method for building an information network via an antenna terminal or an antenna cable disposed in a house for receiving television broadcasting or radio broadcasting, the method comprising:

step (a) of selecting a plurality of frequencies not used by television broadcasting or radio broadcasting in an area where the house is located;

step (b) of dividing transmission data transmitted from a first information terminal into a plurality of channels[.];

step (c) of encoding said transmission data;

step (d) of generating a plurality of carrier waves having the respective frequencies selected in step (a);

step (e) of modulating ~~[(a)]~~said plurality of carrier waves having the respective frequencies selected in step (a) by using the encoded transmission data from the plurality of channels[.]; and

step (f) of transmitting the modulated carrier waves via the antenna terminal or the antenna cable; and

step ~~[(c)]~~(g) of receiving the carrier waves transmitted in step ~~[(b)]~~(f), demodulating the carrier waves to produce reception data over the plurality of channels, and integrating the reception data over the plurality of channels into a single data set which is received by a second information terminal.

8. (Original) The method according to claim 7, wherein, in step (a), at least one of frequencies for channels not used by the television broadcasting or radio broadcasting in an area where the house is located is selected.

9. (Original) The method according to claim 7, further comprising a step of bidirectionally transmitting data between the information network via the antenna terminal or the antenna cable and another network by converting the format of the data.

10. (Currently Amended) A network connection circuit for connecting an information terminal to an antenna terminal or an antenna cable disposed in a house for receiving television broadcasting or radio broadcasting, comprising:

frequency-selecting means for selecting at least one frequency not used by television broadcasting or radio broadcasting in an area where the house is located;

encoding means for encoding transmission data;

carrier generating means for generating a carrier wave having the frequency selected by the frequency-selecting means;

modulating means for modulating said carrier wave using transmission data transmitted from the information terminal; and

transmitting means for ~~modulating a carrier wave having the frequency selected by the frequency-selecting means by using transmission data transmitted from the information terminal and~~ transmitting the modulated carrier wave via the antenna terminal or the antenna cable.

11. (Original) The network connection circuit according to claim 11, wherein at least one of frequencies for channels not used by the television broadcasting or radio broadcasting in an area where the house is located is automatically selected by the frequency-selecting means.

12. (Currently Amended) A network connection circuit for connecting a first information terminal to an antenna terminal or an antenna cable disposed in a house for receiving television broadcasting or radio broadcasting, comprising:

frequency-selecting means for selecting at least one frequency not used by television broadcasting or radio broadcasting in an area where the house is located; [[and]]

receiving means for receiving a carrier wave which has the frequency selected by the frequency-selecting means and has been transmitted from a second information terminal via the antenna terminal or the antenna cable; and

demodulating means for demodulating the carrier wave to produce a baseband signal; and

decoding means for decoding said baseband signal to generate reception data received by the first information terminal.

13. (Original) The network connection circuit according to claim 12, wherein at least one of frequencies for channels not used by the television broadcasting

or radio broadcasting in an area where the house is located is automatically selected by the frequency-selecting means.

14. (Currently Amended) A network connection circuit for connecting a first information terminal to an antenna terminal or an antenna cable disposed in a house for receiving television broadcasting or radio broadcasting, comprising:

frequency-selecting means for selecting a first frequency and a second frequency not used by television broadcasting or radio broadcasting in an area where the house is located;

encoding means for encoding transmission data transmitted from the first information terminal;

carrier generating means for generating a carrier wave having the frequency selected by the frequency-selecting means;

modulating means for modulating said carrier wave using said encoded transmission data;

transmitting means for ~~modulating a carrier wave having the first frequency selected by the frequency-selecting means by using transmission data transmitted from the first information terminal and~~ transmitting the modulated carrier wave via the antenna terminal or the antenna cable; [[and]]

receiving means for receiving a modulated carrier wave which has the second frequency and has been transmitted from a second information terminal via the antenna terminal or the antenna cable [[and]];

demodulating means for demodulating the carrier wave to produce a baseband signal; and

decoding means for decoding said baseband signal to generate reception data received by the first information terminal.

15. (Original) The network connection circuit according to claim 14, wherein at least one of frequencies for channels not used by the television broadcasting or radio broadcasting in an area where the house is located is automatically selected by the frequency-selecting means.

16. (Currently Amended) A network connection circuit for connecting an information terminal to an antenna terminal or an antenna cable disposed in a house for receiving television broadcasting or radio broadcasting, comprising:

frequency-selecting means for selecting a plurality of frequencies not used by television broadcasting or radio broadcasting in an area where the house is located; [[and]]

~~transmitting~~dividing means for dividing transmission data transmitted from the information terminal into a plurality of channels[[,]];

encoding means for encoding said divided transmission data;

modulating means for modulating a plurality of carrier waves having the respective frequencies selected by the frequency-selecting means by using the encoded transmission data from the plurality of channels[[,]]; and

transmitting means for transmitting the modulated carrier waves via the antenna terminal or the antenna cable.

17. (Original) The network connection circuit according to claim 16, wherein at least one of frequencies for channels not used by the television broadcasting or radio broadcasting in an area where the house is located is automatically selected by the frequency-selecting means.

18. (Currently Amended) A network connection circuit for connecting a first information terminal to an antenna terminal or an antenna cable disposed in a house for receiving television broadcasting or radio broadcasting, comprising:

frequency-selecting means for selecting a plurality of frequencies not used by television broadcasting or radio broadcasting in an area where the house is located; and

receiving means for receiving a plurality of carrier waves which have the respective frequencies selected by the frequency-selecting means and have been transmitted from a second information terminal via the antenna terminal or the antenna cable[.];

demodulating means for demodulating the carrier waves to produce a baseband signal;

decoding means for decoding said baseband signal to generate reception data over a plurality of channels[.]; and

integrating means for integrating the reception data over the plurality of channels into a single data set which is received by the first information terminal.

19. (Original) The network connection circuit according to claim 18, wherein at least one of frequencies for channels not used by the television broadcasting or radio broadcasting in an area where the house is located is automatically selected by the frequency-selecting means.

20. (New) The method according to claim 1 comprising:

transmitting said modulated carrier wave from a first network circuit via a first antenna terminal; and

receiving said modulated carrier wave by a second network circuit via a second antenna terminal that is in direct communication with said first antenna terminal via a distributor.

21. (New) The method according to claim 1 comprising:

transmitting said modulated carrier wave from a first antenna terminal to a distributor box; and

receiving said modulated carrier wave by a second antenna terminal from said distributor box.

22. (New) The method according to claim 21 comprising:

directly transmitting said modulated carrier wave from said first antenna terminal to said distributor box; and

directly receiving said modulated carrier wave by said second antenna terminal from said distributor box.

23. (New) The network connection circuit according to claim 10 comprising:

first terminal tuning means for receiving a first carrier wave from a first terminal and for converting said carrier wave to an intermediate-frequency signal;

intermediate frequency means for amplifying said intermediate-frequency signal;

demodulating means for demodulating the amplified intermediate-frequency signal to generate a baseband signal; and

synchronous separation means for separating a synchronous signal based on said baseband signal,

wherein said frequency-selecting means selects said at least one frequency based on said synchronous signal.

24. (New) The network connection circuit according to claim 23 wherein said frequency-selecting means selects a frequency based on said baseband signal.